





PRODUCT DATA

AES-A-408

BOILER WATER OXYGEN SCAVENGER

DESCRIPTION AND USE

AES-A-408 is a tannin based liquid blend designed to react almost instantaneously with oxygen present in the boiler By acting as an oxygen feedwater. scavenger, the product is used to control corrosion and pitting caused by the presence of this dissolved gas.

CHEMICAL FEEDING AND CONTROL

AES-A-408 must be fed continuously to the deaerating heater or feedwater storage tank and may be fed neat directly from the shipping container or mixed in a chemical feed tank. The product cannot be mixed in its concentrated form with most common chemicals used for treatment and hence it should be dosed separately. Stainless steel or plastic is recommended for the chemical feed Copper, copper alloys, and aluminum metallurgy in the chemical feed system must be avoided.

AES-A-408 is normally controlled by a tannin test on the boiler water. Control ranges can vary widely depending upon both makeup water characteristics and system operating conditions and will be specified by the technical representative servicing the facility.

TYPICAL PROPERTIES

Appearance: Dark Amber Liquid

Odor: Characteristic

Specific Gravity: 1.04-1.14

Flash Point: None

pH (undiluted): 4.0 - 6.0 Freeze Point: 0°C(32°F)

(All values approximate)

SAFETY AND HANDLING

Do not take internally. Do not induce vomiting. If ingested, drink at least two glasses of water and get medical Contact with eves causes attention. severe irritation or burns. If eyes are contacted, immediately flush with clear water for 15 minutes and get medical attention. For skin contact, wash with and water. For additional soap information, the Material Safety Data Sheet is available on request.

PACKAGING

AES-A-408 is packaged in 200 and 25liter (nominal volume) plastic drums.

AES TREATMENT PROGRAMS & SERVICES

Cooling Water Treatment Programs

Corrosion Inhibitors

Antiscalants & Antifoulants

Biocides

Antifoams

Boiler Water Treatment Programs

Oxygen Scavengers

Corrosion Inhibitors (Pre-Boiler, Boiler and After

Boiler'

Deposit Inhibitors (Sludge Conditioners)

Antifoams

Alkalinity Builders

Potable Water Treatment Programs

Corrosion Inhibitors

Deposit/ Scale Inhibitors

Disinfectants

Fuel Treatment (Solid & Liquid)

Deposit/ Corrosion Inhibitors

Combustion Catalysts

Coagulants & Flocculants

Organic & Inorganic

Odor Control Programs

Masking Agents

Reactive Odor Control

Enzymes

Hard Surface Cleaners

General Purpose Cleaners

Descalers

Neutralizers

Brewery & Bottling Plants

Pasteurizers

Bottle Washers

Conveyer Chain Lubricants

Metal Treatment Chemicals

Cutting Lubricants

Degreasers

Passivators

Phosphatizing Chemicals

Electroplating Chemicals

R.O. Water Treatment

Scale Inhibitors

Membrane Cleaning Chemicals

ANSI/ NSF Approved Antiscalants

Thermal Desalination Treatment

Scale and Corrosion Inhibitors

Antifoams

Descalers

Steam & Condensate Programs

Corrosion Control

USDA/ FDA Approved Additives

Raw Water & Wastewater Programs

Coagulants Odor control

Flocculants Enzymes

Disinfectants Bacterial Spores

Antifoams Emulsion Breakers

Process Treatment Programs

Specialty Chemical Additives

Commercial Laundry Chemicals

Built Detergents

Emulsifiers

Fabric Softeners

Peroxide Bleach

Chlorine Bleach

Scoring Agents

Services

Technical & Engineering Consultations

Analytical Services

Ion Exchange Resins Evaluation

Reverse Osmosis Cleaning

Equipment Supply

Water & Wastewater Treatment Plants

Filters, Pumps

Tanks

Chemical Feed Systems

PH Controllers

Blow down Controllers

Automatic Control Systems

SCADA

Manufactured in the Kingdom of Saudi Arabia by :



AES ARABIA LTD

Environmental & Process Engineering

P.O. Box 105689, Riyadh 11656, Kingdom of Saudi Arabia Phone: 966 11 4772398 Fax: 966 11 4785456 e-mail: info@aesarabia.com www.aesarabia.com