

AES ARABIA LTD



Environmental & Process Engineering

PRODUCT DATA

AES-A-902M CATIONIC POLYELECTROLYTE

DESCRIPTION

AES-A-902M is a liquid cationic flocculent which works effectively as primary coagulant in the clarification of water and oily waste. The ingredients of AES-A-902M are approved for use in potable water treatment in the United States and the United Kingdom.

ADVANTAGES

- Easy to apply. Pourable liquid, which simplifies dilution, feed and handling operations
- Economical. Effective at low dosage levels resulting in reduced handling and storage costs.
- Eliminates inorganic flocculants.
- Forms low volume sludge.
- Requires less frequent sludge blow-down.
- Increases time between filter backwashes.
- Effective over wide pH range and eliminates need for pH adjustment.
- Removes turbidity and color from water.
- Immediately soluble in water at all concentrations.
- Non-corrosive.
- Improves solids capture and clarity of filtrate or supernatant.

PRINCIPAL USES:

- Replaces inorganic salts as primary coagulant in influent and effluent treatment.
- Can be applied in Gravity settling, Clarifiers, Air Flotation separation, direct filtration - pressure and gravity, drying beds, dewatering by vacuum filter or filter belt.
- Pre-treatment of water for Reverse Osmosis, and Hyperfilteration and secondary oil recovery.
- Treatment of effluent waters containing organic matter, cellulose, and oil.
- Improving clarity from inorganic settlement operations.
- Sewage sludge treatment.
- Food Industry.
- Treatment of highly organic wastes.

TREATMENT LEVELS

Primary Coagulant: 1 - 40 mg/l Coagulant aid: 0.2 - 10mg/l Flotation: 1 - 40 mg/l

TYPICAL PROPERTIES

Appearance: Clear Colourless To Pale Yellow or Amber Liquid Specific Gravity: 1.02 - 1.08 pH (as supplied): 3.0 - 6.0 Solubility in water: Completely Soluble (All values approximate)

APPLICATION

The product should be metered to the system using a corrosion resistant positive displacement pump at a concentration of 1% or less. Dissolution is possible via in-line dilution with water.

HANDLING

The product has a low order of toxicity and is not irritating to skin or eye. Consequently only normal measures of personal hygiene and plant housekeeping should be needed in handling this product. Spills are slippery and should be flushed immediately with water.

PACKAGING

AES-A-902M is available in 200 and 25 liter (nominal volume) plastic drums.

Information given above may be amended without notice.

Issue#: Issue Date Feb. 12, 17

AES TREATMENT PROGRAMS & SERVICES

Cooling Water Treatment Programs

Corrosion Inhibitors

Antiscalants & Antifoulants

Biocides

Antifoams

Boiler Water Treatment Programs

Oxygen Scavengers

Corrosion Inhibitors (Pre-Boiler, Boiler and After

Boiler'

Deposit Inhibitors (Sludge Conditioners)

Antifoams

Alkalinity Builders

Potable Water Treatment Programs

Corrosion Inhibitors

Deposit/ Scale Inhibitors

Disinfectants

Fuel Treatment (Solid & Liquid)

Deposit/ Corrosion Inhibitors

Combustion Catalysts

Coagulants & Flocculants

Organic & Inorganic

Odor Control Programs

Masking Agents

Reactive Odor Control

Enzymes

Hard Surface Cleaners

General Purpose Cleaners

Descalers

Neutralizers

Brewery & Bottling Plants

Pasteurizers

Bottle Washers

Conveyer Chain Lubricants

Metal Treatment Chemicals

Cutting Lubricants

Degreasers

Passivators

Phosphatizing Chemicals

Electroplating Chemicals

R.O. Water Treatment

Scale Inhibitors

Membrane Cleaning Chemicals

ANSI/ NSF Approved Antiscalants

Thermal Desalination Treatment

Scale and Corrosion Inhibitors

Antifoams

Descalers

Steam & Condensate Programs

Corrosion Control

USDA/ FDA Approved Additives

Raw Water & Wastewater Programs

Coagulants Odor control

Flocculants Enzymes

Disinfectants Bacterial Spores

Antifoams Emulsion Breakers

Process Treatment Programs

Specialty Chemical Additives

Commercial Laundry Chemicals

Built Detergents

Emulsifiers

Fabric Softeners

Peroxide Bleach

Chlorine Bleach

Scoring Agents

Services

Technical & Engineering Consultations

Analytical Services

Ion Exchange Resins Evaluation

Reverse Osmosis Cleaning

Equipment Supply

Water & Wastewater Treatment Plants

Filters, Pumps

Tanks

Chemical Feed Systems

PH Controllers

Blow down Controllers

Automatic Control Systems

SCADA

Manufactured in the Kingdom of Saudi Arabia by :



AES ARABIA LTD

Environmental & Process Engineering

P.O. Box 105689, Riyadh 11656, Kingdom of Saudi Arabia Phone: 966 11 4772398 Fax: 966 11 4785456 e-mail: info@aesarabia.com www.aesarabia.com