



PRODUCT DATA

AES-1535 COOLING WATER MICROBIOCIDE

DESCRIPTION AND USE

AES-1535 is a concentrated quaternary based algaecide for use in recirculating cooling tower water systems. The product is effective over a wide pH range against algae, fungi, and slime forming bacteria typically found in these systems.

Unlike most similar products, it is an exceptional wetting agent and, at normal use concentrations, it will cause only minimum foaming in the treated systems. It is compatible with most water treatment formulations but should not be used with soap, sulfated oils or anionic surfactants.

CHEMICAL FEEDING AND CONTROL

AES-1535 is normally shot fed to the system to be treated one (1) to three (3) times per week or as required to maintain control. Often, alternating the material with another type of microbiocide, either oxidizing or non-oxidizing will enhance the performance of both materials. The product should be added to the system at a point where rapid mixing will occur.

AES-1535 is typically required at the rate of 3.0 to 8.0 fl.ozs/1000 gallons water (25 - 60 mg/l product) in the recirculating cooling system to be treated. There is a field test available to check the concentration of the product in the system; however, system volume should be determined prior to application to assure proper additions are made. If necessary, increase the treatment frequency to bring the system under control. Badly fouled systems should be

cleaned prior to treatment.

TYPICAL PROPERTIES

Appearance: Clear light yellow liquid

Odor: Mild characteristic

Specific Gravity: 0.97 – 1.02

pH (undiluted): 4.0-9.0

SAFETY AND HANDLING

AES-1535 is moderately toxic if ingested. **DO NOT TAKE INTERNALLY.** If ingested, drink several glasses of milk, egg whites, gelatin solution or water. **DO NOT** induce vomiting. **GET IMMEDIATE MEDICAL ATTENTION.** Contact with eyes causes irritation. If eyes are contacted, immediately flush with clear water for 15 minutes and if irritation persists, get medical attention. If skin is contacted, immediately wash with soap and water. Change and launder contaminated clothing before reuse. The use of goggles or face shield and rubber gloves when handling this product is recommended. For more information, the Material Safety Data Sheet is available on request

PACKAGING

AES-1535 is packaged in 200 and 25 liter (nominal volume) non-returnable plastic drums.

Information given above may be amended without notice.

Issue#: 1/1 Issue Date: Feb. 6, 17

AES TREATMENT PROGRAMS & SERVICES

Cooling Water Treatment Programs

Corrosion Inhibitors
Antiscalants & Antifoulants
Biocides
Antifoams

Boiler Water Treatment Programs

Oxygen Scavengers
Corrosion Inhibitors (Pre-Boiler, Boiler and After
Boiler)
Deposit Inhibitors (Sludge Conditioners)
Antifoams
Alkalinity Builders

Potable Water Treatment Programs

Corrosion Inhibitors
Deposit/ Scale Inhibitors
Disinfectants

Fuel Treatment (Solid & Liquid)

Deposit/ Corrosion Inhibitors
Combustion Catalysts

Coagulants & Flocculants

Organic & Inorganic

Odor Control Programs

Masking Agents
Reactive Odor Control
Enzymes

Hard Surface Cleaners

General Purpose Cleaners
Descalers
Neutralizers

Brewery & Bottling Plants

Pasteurizers
Bottle Washers
Conveyer Chain Lubricants

Metal Treatment Chemicals

Cutting Lubricants
Degreasers
Passivators
Phosphatizing Chemicals
Electroplating Chemicals

R.O. Water Treatment

Scale Inhibitors
Membrane Cleaning Chemicals
ANSI/ NSF Approved Antiscalants

Thermal Desalination Treatment

Scale and Corrosion Inhibitors
Antifoams
Descalers

Steam & Condensate Programs

Corrosion Control
USDA/ FDA Approved Additives

Raw Water & Wastewater Programs

Coagulants Odor control
Flocculants Enzymes
Disinfectants Bacterial Spores
Antifoams Emulsion Breakers

Process Treatment Programs

Specialty Chemical Additives

Commercial Laundry Chemicals

Built Detergents
Emulsifiers
Fabric Softeners
Peroxide Bleach
Chlorine Bleach
Scoring Agents

Services

Technical & Engineering Consultations
Analytical Services
Ion Exchange Resins Evaluation
Reverse Osmosis Cleaning

Equipment Supply

Water & Wastewater Treatment Plants
Filters, Pumps
Tanks
Chemical Feed Systems
PH Controllers
Blow down Controllers
Automatic Control Systems
SCADA

Manufactured in the Kingdom of Saudi Arabia by:

The logo for AES, featuring the letters 'AES' in a bold, italicized, red font with a white outline.

AES ARABIA LTD

Environmental & Process Engineering

P.O. Box 105689, Riyadh 11656, Kingdom of Saudi Arabia

Phone: 966 11 4772398 Fax: 966 11 4785456

e-mail: info@aesarabia.com

www.aesarabia.com

In